



\*可选配件



### 产品特性

灯具颜色: 金属灰+白色面板  
 主体材质: 压铸铝  
 光学系统: 透镜  
 灯具外观: 金属质感  
 投射方向: 水平0-355°  
 防护等级: IP20 可选配IP44防水组件  
 环境温度: -20°~40°  
 重量: 121g

### 产品规格

开孔尺寸: ∅55mm  
 功率: 10W  
 光束角度: 15°, 24°, 36°, 60°  
 天花厚度: 2mm-25mm  
 安装方式: 嵌入式  
 吊顶空间: 大于100mm  
 防眩角度: 40°

输入电压: 220-240V~50Hz  
 输入电流: 45mA  
 显指: Ra92  
 色温: 2700K、3000K、3500K、4000K  
 光通量: 525lm、547lm、586lm、674lm (15°)  
 584lm、609lm、651lm、676lm (24°)  
 622lm、648lm、693lm、719lm (36°)  
 540lm、563lm、602lm、625lm (60°)

以下可调光款为可控硅调光, 0-10V调光:T改为M

色温	型号	h(m)	D(cm)	average (lx)	center (lx)	光分布图
2700K	TSF5055W10-TB2715	1.0	29	3290	4724	15°
	TSF5055W10-NB2715	2.0	57	823	1181	
		3.0	86	366	525	
		4.0	114	206	295	
3000K	TSF5055W10-TB3015	1.0	29	3428	4920	15°
	TSF5055W10-NB3015	2.0	57	857	1230	
		3.0	86	381	547	
		4.0	114	214	308	
3500K	TSF5055W10-TB3515	1.0	29	3668	5265	15°
	TSF5055W10-NB3515	2.0	57	917	1316	
		3.0	86	408	585	
		4.0	114	229	329	
4000K	TSF5055W10-TB4015	1.0	29	4223	6062	15°
	TSF5055W10-NB4015	2.0	57	1056	1516	
		3.0	86	469	674	
		4.0	114	264	379	
2700K	TSF5055W10-TB2724	1.0	39	2093	3055	24°
	TSF5055W10-NB2724	2.0	79	523	764	
		3.0	118	233	340	
		4.0	158	131	191	
3000K	TSF5055W10-TB3024	1.0	39	2180	3183	24°
	TSF5055W10-NB3024	2.0	79	545	796	
		3.0	118	242	354	
		4.0	158	136	199	
3500K	TSF5055W10-TB3524	1.0	39	2332	3405	24°
	TSF5055W10-NB3524	2.0	79	583	851	
		3.0	118	259	378	
		4.0	158	146	213	
4000K	TSF5055W10-TB4024	1.0	39	2419	3533	24°
	TSF5055W10-NB4024	2.0	79	605	883	
		3.0	118	269	393	
		4.0	158	151	221	
2700K	TSF5055W10-TB2736	1.0	62	1028	1571	36°
	TSF5055W10-NB2736	2.0	123	257	393	
		3.0	184	114	175	
		4.0	246	64	98	
3000K	TSF5055W10-TB3036	1.0	62	1071	1636	36°
	TSF5055W10-NB3036	2.0	123	268	409	
		3.0	184	119	182	
		4.0	246	67	102	
3500K	TSF5055W10-TB3536	1.0	62	1146	1751	36°
	TSF5055W10-NB3536	2.0	123	287	438	
		3.0	184	127	195	
		4.0	246	72	109	
4000K	TSF5055W10-TB4036	1.0	62	1189	1816	36°
	TSF5055W10-NB4036	2.0	123	297	454	
		3.0	184	132	202	
		4.0	246	74	114	
2700K	TSF5055W10-TB2760	1.0	91	520	784	60°
	TSF5055W10-NB2760	2.0	181	130	196	
		3.0	271	58	87	
		4.0	362	33	49	
3000K	TSF5055W10-TB3060	1.0	91	542	817	60°
	TSF5055W10-NB3060	2.0	181	136	204	
		3.0	271	60	91	
		4.0	362	34	51	
3500K	TSF5055W10-TB3560	1.0	91	580	874	60°
	TSF5055W10-NB3560	2.0	181	145	219	
		3.0	271	64	97	
		4.0	362	36	55	
4000K	TSF5055W10-TB4060	1.0	91	602	907	60°
	TSF5055W10-NB4060	2.0	181	150	227	
		3.0	271	67	101	
		4.0	362	38	57	